Safety Data Sheet
acc. to OSHA HCS

Printing date 06/05/2025 Reviewed on 03/11/2025

* 1 Identification

· **Product identifier**

· **Trade name:** **Wecryl 810 (ALT R290)**

· **Other means of identification**

· **Application of the substance / the mixture** Putty

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

WestWood USA/
ALT Global, LLC
12 Dwight Place
Fairfield, NJ 07004
USA
Tel.: +1 973-287-6158
Internet: www.westwood-usa.com

· **Information department:**

Division product safety
Mr. Bonyadlou
Tel.: +1 973-287-6158
E-Mail: mbonyadlou@westwood-usa.com

· **Emergency telephone number:**

For Chemical Emergency
Spill Leak Fire Exposure or Accident
Call CHEMTREC Day or Night

DOMESTIC NORTH AMERICA 800-424-9300
INTERNATIONAL, CALL 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

· **Classification of the substance or mixture**

GHS02 Flame

Flammable liquids 3	H226 Flammable liquid and vapor.

GHS07

Skin irritation 2	H315 Causes skin irritation.
Sensitization - skin 1	H317 May cause an allergic skin reaction.
Specific target organ toxicity (single exposure) 3	H335 May cause respiratory irritation.

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS02 GHS07

(Contd. on page 2)

(Contd. of page 1)

· **Signal word** Warning

· **Hazard-determining components of labeling:**
Methyl methacrylate
2-ethylhexyl acrylate
Diethanol-p-toluidine
Fatty acid, C 18 - unsaturated, dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine

· **Hazard statements**
H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

· **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapors.
P280	Wear protective clothing/ eye protection.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P312	Call a poison center/doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

· **Information pertaining to particular dangers for man and environment:**

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**

Health = 1
Fire = 3
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1
Fire = 3
Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).

· **vPvB:** Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

· **Classification according to (d)(1)(ii) of § 1910.1200**
The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

· **Hazards not otherwise classified**
There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 80-62-6 Index number: 607-033-00-5	Methyl methacrylate	≥10-≤30%

(Contd. on page 3)

(Contd. of page 2)

CAS: 103-11-7 Index number: 607-107-00-7	2-ethylhexyl acrylate	≥10-≤13%
	Diethanol-p-toluidine	≥0.1-<1%
CAS: 162627-17-0	Fatty acid, C 18 - unsaturated, dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine	≥0.1-<1%

4 First-aid measures

· **Description of first aid measures**
· **General information:**
Immediately remove any clothing soiled by the product.
Take affected persons out of danger area and lay down.
Involve doctor immediately.
· **After inhalation:**
In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.
Seek medical treatment.
· **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
· **After swallowing:** Do not induce vomiting; immediately call for medical help.
· **Most important symptoms and effects, both acute and delayed**
Headache
Dizziness
Skin sensitization.
Irritant to skin, eyes and respiratory system.
· **Indication of any immediate medical attention and special treatment needed**
After inhalation, even in the absence of signs of disease, inhaled corticosteroid (eg Ventolair) give.

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:** Carbon dioxide, sand, extinguishing powder, foam.
· **For safety reasons unsuitable extinguishing agents:** Water with full jet
· **Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
Carbon monoxide (CO)
Nitrogen oxides (NOx)
Vapours are heavier than air.
Crawling vapors can result in greater distance from the ignition!
· **Advice for firefighters**
· **Protective equipment:**
Wear fully protective suit.
Wear self-contained respiratory protective device.
· **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

(Contd. on page 4)

(Contd. of page 3)

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation

Keep away from ignition sources

Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.

· **Methods and material for containment and cleaning up:**
Do not flush with water or aqueous cleansing agents
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
21645-51-2	aluminium hydroxide	8.7 mg/m³
80-62-6	Methyl methacrylate	17 ppm
103-11-7	2-ethylhexyl acrylate	15 ppm
112945-52-5	SYNTHETIC AMORPHOUS SILICA	18 mg/m³
	Polyethylenglykoldimethacrylat	30 mg/m³
13463-67-7	titanium dioxide	30 mg/m³
14808-60-7	Quartz (SiO2)	0.075 mg/m³
1317-61-9	C.I.Pigment black 11	21 mg/m³
107-98-2	1-methoxy-2-propanol	100 ppm
20344-49-4	iron hydroxide oxide	24 mg/m³
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
818-61-1	2-hydroxyethyl acrylate	2.0 ppm
1314-23-4	zirconium oxide	14 mg/m³
123-86-4	n-butyl acetate	5 ppm
1344-28-1	aluminium oxide	15 mg/m³
7631-86-9	silicon dioxide, chemically prepared	18 mg/m³
7447-41-8	lithium chloride	2.3 mg/m³
97-88-1	n-butyl methacrylate	19 mg/m³
67-56-1	methanol	530 ppm
67-68-5	dimethyl sulfoxide	150 ppm

· **PAC-2:**		
21645-51-2	aluminium hydroxide	73 mg/m³
80-62-6	Methyl methacrylate	120 ppm
103-11-7	2-ethylhexyl acrylate	120 ppm
112945-52-5	SYNTHETIC AMORPHOUS SILICA	100 mg/m³
	Polyethylenglykoldimethacrylat	330 mg/m³
13463-67-7	titanium dioxide	330 mg/m³
14808-60-7	Quartz (SiO2)	8.3 mg/m3
1317-61-9	C.I.Pigment black 11	230 mg/m³

(Contd. on page 5)

Trade name: Wecryl 810 (ALT R290)

(Contd. of page 4)

107-98-2	1-methoxy-2-propanol	160 ppm
20344-49-4	iron hydroxide oxide	260 mg/m³
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
818-61-1	2-hydroxyethyl acrylate	3.6 ppm
1314-23-4	zirconium oxide	110 mg/m³
123-86-4	n-butyl acetate	200 ppm
1344-28-1	aluminium oxide	41 ppm
7631-86-9	silicon dioxide, chemically prepared	200 ppm
7447-41-8	lithium chloride	17 mg/m3
97-88-1	n-butyl methacrylate	210 mg/m³
67-56-1	methanol	2100 ppm
67-68-5	dimethyl sulfoxide	290 ppm

· **PAC-3:**

21645-51-2	aluminium hydroxide	440 mg/m³
80-62-6	Methyl methacrylate	570 ppm
103-11-7	2-ethylhexyl acrylate	150 ppm
112945-52-5	SYNTHETIC AMORPHOUS SILICA	630 mg/m³
	Polyethylenglykoldimethacrylat	2,000 mg/m³
13463-67-7	titanium dioxide	2,000 mg/m³
14808-60-7	Quartz (SiO2)	50 mg/m3
1317-61-9	C.I.Pigment black 11	1,400 mg/m³
107-98-2	1-methoxy-2-propanol	660 ppm
20344-49-4	iron hydroxide oxide	1,600 mg/m³
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
818-61-1	2-hydroxyethyl acrylate	21 ppm
1314-23-4	zirconium oxide	680 mg/m³
123-86-4	n-butyl acetate	3000* ppm
1344-28-1	aluminium oxide	240 ppm
7631-86-9	silicon dioxide, chemically prepared	1200 ppm
7447-41-8	lithium chloride	100 mg/m3
97-88-1	n-butyl methacrylate	1,300 mg/m³
67-56-1	methanol	7200 ppm
67-68-5	dimethyl sulfoxide	1,800 ppm

· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· **Precautions for safe handling**
Cool down container when heated. Cool containers exposed to heat with water. Emergency cooling must be provided in the event of an ambient fire. Keep container tightly closed to prevent heat build up (pressure increase). Avoid heat.
Do not refill residue into storage receptacles.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
at least 7-fold air changes per hour

(Contd. on page 6)

(Contd. of page 5)

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**
Highly volatile, flammable constituents are released during processing.
Keep ignition sources away - Do not smoke.
Fumes can combine with air to form an explosive mixture.
Only explosion-proof equipment.
Protect against electrostatic charges.
Protect from heat.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:**
Store only in the original receptacle.
Store in a cool location.
· **Information about storage in one common storage facility:**
Store away from oxidizing agents.
Store away from foodstuffs.
· **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Storage in a collecting room is required.
Store under lock and key and with access restricted to technical experts or their assistants only.
max. Storage temperature 30 ° C
Keep receptacle tightly sealed.
Protect from heat and direct sunlight.
· **Specific end use(s)** Building coating or sealing.

8 Exposure controls/personal protection

· **Control parameters**
· **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

80-62-6 Methyl methacrylate (10-30%)	
PEL	Long-term value: 410 mg/m³, 100 ppm
REL	Long-term value: 410 mg/m³, 100 ppm
TLV	Short-term value: 410 mg/m³, 100 ppm Long-term value: 205 mg/m³, 50 ppm DSEN, A4
112945-52-5 SYNTHETIC AMORPHOUS SILICA (1-5%)	
OSHA PEL	Short-term value: 15 mg/m³ Long-term value: 5 mg/m³
TLV-TWA	Short-term value: 10 mg/m³ Long-term value: 3 mg/m³ ACGIH

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Appropriate engineering controls** No further data; see section 7.
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Avoid contact with the eyes and skin.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.

(Contd. on page 7)

(Contd. of page 6)

Keep away from foodstuffs, beverages and feed.

· **Breathing equipment:**
Ensure good ventilation.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Preventive skin protection by use of skin-protecting agents is recommended.
After use of gloves apply skin-cleaning agents and skin cosmetics.
Check protective gloves prior to each use for their proper condition.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
General recommendation: The usage time of the protective gloves is approx. 50% of the penetration time measured in the laboratory!

· **Material of gloves**

Butyl rubber gloves - butyl e.g. KCL BUTOJET
Recommended thickness of the material: ≥ 0.7 mm
Breakthrough time: ≥ 480 min

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**
Our Recommendation is mainly on a one-time use as a short-term protection Liquid splashes. For other applications, you should contact a glove manufacturer.
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**
Butyl rubber, BR

· **For the permanent contact gloves made of the following materials are suitable:** Butyl rubber, BR

· **Not suitable are gloves made of the following materials:** Leather gloves

· **Eye protection:**

Tightly sealed goggles

· **Body protection:**

Protective work clothing

(Contd. on page 8)

(Contd. of page 7)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Physical state**	Liquid
· **Color:**	Different according to coloring
· **Odor:**	Ester-like
· **Odor threshold:**	Not determined.
· **Melting point/Melting range:**	Undetermined.
· **Boiling point/Boiling range:**	101 °C (213.8 °F)
· **Flammability:**	Not applicable. Flammable.
· **Explosion limits:**	
· **Lower:**	Not determined.
· **Upper:**	Not determined.
· **Flash point:**	28 °C (82.4 °F)
· **Auto igniting:**	252 °C (485.6 °F)
· **Decomposition temperature:**	Not determined.
· **pH-value:**	Not determined. Mixture is non-polar/aprotic.
· **Viscosity:**	
· **Kinematic at 20 °C (68 °F):**	3,358 mm²/s (EN ISO 2431)
· **Dynamic at 20 °C (68 °F):**	4,500 mPas (EN ISO 2555)
· **Solubility in / Miscibility with**	
· **Water:**	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	log Pow: 4,29 (2-EHA); (25 °C, OECD 107) log Pow: 1,38 (MMA)
· **Vapor pressure:**	Not determined.
· **Vapor pressure:**	
· **Density at 20 °C (68 °F):**	1.34 g/cm³ (11.18 lbs/gal) (EN ISO 2811-1)
· **Relative density**	Not determined.
· **Vapor density**	Not determined.
· **Particle characteristics**	Not applicable.

· **Other information**	
· **Appearance:**	
· **Form:**	Pasty
· **Important information on protection of health and environment, and on safety.**	
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product is not explosive. However, formation of explosive air/vapor mixtures are possible. Not determined.
· **Solvent content:**	
· **Organic solvents:**	0.1 %
· **VOC content:**	≥0.08-<0.12 % 1.7 g/l / 0.01 lb/gal
· **Solids content:**	72.0 %
· **Change in condition**	
· **Evaporation rate**	Not determined.

(Contd. on page 9)

(Contd. of page 8)

10 Stability and reactivity

· **Reactivity** see Section 10.2
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions**
Exothermic reaction.
Reacts with peroxides and other radical forming substances.
A hazardous polymerization may occur after the exhaustion of the inhibitor.
· **Conditions to avoid** Avoid heat. Avoid direct sunlight.
· **Incompatible materials:** Violent reactions with peroxides and other reducing agents
· **Hazardous decomposition products:** No hazardous decomposition products when used as directed.
· **Additional information:**
Emergency procedures will vary depending on individual circumstances. The customer should have a contingency plan to the workplace may be present.

11 Toxicological information

· **Information on toxicological effects** There were no toxicological findings to the mixture.
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
ATE (Acute Toxicity Estimate)		
Oral	LD50	38,922 mg/kg

21645-51-2 aluminium hydroxide		
Oral	LD50	>2,000 mg/kg (rat)
	NOAEL	30 mg/kg (rat) chronisch
Inhalative	LC50	7.6 mg/l (rat)
	NOAEC	70 mg/m³ (rat)
14808-60-7 Quarzsand		
Oral	LD50	>1,234,567 mg/kg
	LD50	>1,234,567 mg/kg
80-62-6 Methyl methacrylate		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
	NOAEL	2,000 ppm (rat) drinking water, 6-2000 ppm Findings: No toxic effects
	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (hare)
	LC50	>5,000 mg/kg (Rabbit)
	LD50	>5,000 mg/kg (hare)
Inhalative	NOAEL	25 ppm (rat) 25 - 400 ppm Findings: Damage to mucous membranes in the nose at 400 ppm
	LC50/4h	29.8 mg/l (rat)
103-11-7 2-ethylhexyl acrylate		
Oral	LD50	4,435 mg/kg (rat) (BASF-Test)

(Contd. on page 10)

(Contd. of page 9)

Dermal	LD50	4,435 mg/kg (rat)
	LD50	7,522 mg/kg (hare)
	LC50	7,520 mg/kg (hare)
	LD50	7,522 mg/kg (hare)
Diethanol-p-toluidine		
Oral	LD50	100 mg/kg (ATE)

· **Primary irritant effect:**
· **on the skin:**
Irritant effect
Irritant to skin and mucous membranes.
· **on the eye:** Irritating effect.
· **Sensitization:** Sensitization possible through skin contact.
· **Other information (about experimental toxicology):**
Due to the high vapor pressure is a harmful concentration in the air quickly been reached. At high concentrations can occur narcotic effect.
· **Subacute to chronic toxicity:** not tested
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
· **Interactive effects** No interactive effects between components are known.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**		
80-62-6	Methyl methacrylate	3
103-11-7	2-ethylhexyl acrylate	2B
13463-67-7	titanium dioxide	2B
14808-60-7	Quartz (SiO2)	1
128-37-0	Butylhydroxytoluene	3
7631-86-9	silicon dioxide, chemically prepared	3
97-88-1	n-butyl methacrylate	2B

· **NTP (National Toxicology Program)**		
14808-60-7	Quartz (SiO2)	K

· **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

· **Alternative sources for toxicological information**
No non-standard sources for toxicological information where used.

12 Ecological information

· **Toxicity**	
80-62-6 Methyl methacrylate	
EC3/16h	100 mg/l (Pseudomonas putida) (Cell proliferation inhibition test, Bringmann-Kühn)
EC50/21d	49 mg/l (daphnia)
103-11-7 2-ethylhexyl acrylate	
EC50/21d	0.5 mg/l (daphnia)

(Contd. on page 11)

(Contd. of page 10)

· **Aquatic toxicity:**	
21645-51-2 aluminium hydroxide	
EC50	>100 mg/l (daphnia magna)
	>100 mg/l (Selenastrum capricornutum)
LC50	>100 mg/l (salmon)
80-62-6 Methyl methacrylate	
EC50	170 mg/l (aquatic algae and cyanobacteria)
EC50/48h	69 mg/l (daphnia)
	69 mg/l (daphnia magna) (OECD 202)
LC50/96h	>79 mg/l (aquatic vertebrates - in vivo)
	>79 mg/l (Rainbow trout) (OECD 203)
ErC50/72h	>110 mg/l (alga)
	>110 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC/72h	49 mg/l (alga)
	>110 mg/l (Selenastrum capricornutum) (OECD 201)
NOEC/21d	37 mg/l (daphnia)
EC50/72h	>110 mg/l (Selenastrum capricornutum) (OECD 201)
EC0	100 mg/l (eschrichia coli)
NOEC	9.4 mg/l (Danio rerio) (OECD 210) fish early life stage test, 35 days
	37 mg/l (daphnia magna) (OECD 211) 21 days
103-11-7 2-ethylhexyl acrylate	
other (28d)	>1,000 mg/kg (Soil microorganisms) (OECD 217) The product has not been tested. The statement has been derived from products of a similar structure or composition.
EC50/48h	1.3 mg/l (daphnia)
	1.3 mg/l (daphnia magna) (OECD-Richtline 202) Part 1
LC50/96h	1.81 mg/l (aquatic vertebrates - in vivo)
	1.81 mg/l (fish)
	1.81 mg/l (Rainbow trout) (OECD 203)
ErC50/72h	1.71 mg/l (alga)
NOEC/21d	0.19 mg/l (daphnia)
	0.19 mg/l (daphnia magna) The details of the toxic effect relates to the analytically determined concentration. The product has not been tested. The statement has been derived from products of a similar structure or composition.
EC50/72h (static)	1.71 mg/l (scenedesmus subspicatus) (OECD 201) Die Angaben der toxischen Wirkung bezieht sich auf die analytisch ermittelte Konzentration.

· **Persistence and degradability** No further relevant information available.
· **Other information:** The product is easily biodegradable.
· **Bioaccumulative potential** May be accumulated in organism
· **Mobility in soil**
MMA: A binding to the solid phase of soil, sediment and sewage sludge is not expected. From the water surface the substance is slowly evaporated into the atmosphere. Where the substance into the environment he verleibt preferably in the compartment into which it has emerged.

(Contd. on page 12)

(Contd. of page 11)

2-EHA: The product floats on water and does not dissolve. Adsorption on soil is not likely.

· **Results of PBT and vPvB assessment**
· **PBT:** Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).
· **vPvB:** Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).
· **Other adverse effects**
· **Additional ecological information:**
· **CSB-value:** 2-EHA: Theoretical oxygen demand (TOD) = 5.6 g/g
· **BSB5-value:** 0.14 g/g (MMA)
· **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

· **Waste treatment methods**
Hazardous waste according to Waste Catalogue (EWC). If recycling is not possible, waste must be in compliance with local regulations to be removed.
· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncured product residues are special waste.
Cured product residues are not hazardous waste.

· **Uncleaned packagings:**
· **Recommendation:**
This product (liquid) and its container must be disposed of as hazardous waste.
Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**	
· **DOT, IATA**	UN1263
· **ADR, ADN, IMDG**	Void
· **UN proper shipping name**	
· **DOT**	Paint
· **ADR, ADN, IMDG**	Void
· **IATA**	PAINT
· **Transport hazard class(es)**	
· **DOT**	

· **Class**	3 Flammable liquids
· **Label**	3

(Contd. on page 13)

(Contd. of page 12)

· **ADR, ADN, IMDG**	
· **Class**	Void
· **IATA**	
· **Class**	3 Flammable liquids
· **Label**	3
· **Packing group**	
· **DOT, IATA**	III
· **ADR, IMDG**	Void
· **Environmental hazards:**	
· **Marine pollutant:**	No
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable.
· **Transport/Additional information:**	
· **DOT**	
· **Remarks:**	Classification according to viscosity clause [(173.120 (2)(d) and 173.121 (b) (iv)]
· **ADR**	
· **Remarks:**	> 450 l: 3 F1, III
· **IMDG**	
· **Remarks:**	> 450 l: 3, III
· **Special precautions for user**	Not applicable.
· **UN "Model Regulation":**	Void

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· **Section 355 (extremely hazardous substances):**
None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**	
80-62-6	Methyl methacrylate
1344-28-1	aluminium oxide
67-56-1	methanol

· **TSCA (Toxic Substances Control Act):**		
21645-51-2	aluminium hydroxide	ACTIVE
80-62-6	Methyl methacrylate	ACTIVE
103-11-7	2-ethylhexyl acrylate	ACTIVE
	Polyethylenglykoldimethacrylat	ACTIVE
13463-67-7	titanium dioxide	ACTIVE

(Contd. on page 14)

(Contd. of page 13)

14808-60-7	Quartz (SiO2)	ACTIVE
103671-44-9	N,N-Bis-(2-hydroxyethyl)-p-toluidine	ACTIVE
1317-61-9	C.I.Pigment black 11	ACTIVE
	3-(2H-Benzotriazol-2-yl)-5-(1,1-di-methylethyl)-4-hydroxy-, verzweigte und lineare C7-9-Alkylester	ACTIVE
107-98-2	1-methoxy-2-propanol	ACTIVE
20344-49-4	iron hydroxide oxide	ACTIVE
8002-74-2	Paraffin waxes and Hydrocarbon waxes	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
128-37-0	Butylhydroxytoluene	ACTIVE
818-61-1	2-hydroxyethyl acrylate	ACTIVE
	Silan, dichlordimethyl-, Reaktionsprodukte mit Siliciumdioxid	ACTIVE
1314-23-4	zirconium oxide	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
1344-28-1	aluminium oxide	ACTIVE
7631-86-9	silicon dioxide, chemically prepared	ACTIVE
7447-41-8	lithium chloride	ACTIVE
97-88-1	n-butyl methacrylate	ACTIVE
67-56-1	methanol	ACTIVE
67-68-5	dimethyl sulfoxide	ACTIVE

· **Hazardous Air Pollutants**

80-62-6	Methyl methacrylate
67-56-1	methanol

· **Proposition 65**

· **Chemicals known to cause cancer:**

103-11-7	2-ethylhexyl acrylate
14808-60-7	Quartz (SiO2)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

67-56-1	methanol

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

80-62-6	Methyl methacrylate	E, NL

· **TLV (Threshold Limit Value)**

80-62-6	Methyl methacrylate	A4
13463-67-7	titanium dioxide	A4
14808-60-7	Quartz (SiO2)	A2
128-37-0	Butylhydroxytoluene	A4
1314-23-4	zirconium oxide	A4
1344-28-1	aluminium oxide	A4

(Contd. on page 15)

(Contd. of page 14)

· NIOSH-Ca (National Institute for Occupational Safety and Health)	
13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO2)

· **National regulations:**

· **Information about limitation of use:**
Employment restrictions concerning young persons must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*16 Other information

These figures relate to the product as delivered.

Sector of Use
Relevant identified uses of the mixture
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU19 Building and construction work
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against
SU21 Consumer uses: Private households / general public / consumers

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Training hints**
Teaching about hazards and precautions to hand the operating instructions (Technical Rule 555). Instruction must take place before the start of employment and at least annually thereafter.

· **Version number of previous version:** 25

· **Date of preparation** 06/05/2025

· **Abbreviations and acronyms:**
ICAO: International Civil Aviation Organisation
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flammable liquids 3: Flammable liquids – Category 3
Skin irritation 2: Skin corrosion/irritation – Category 2
Sensitization - skin 1: Skin sensitisation – Category 1
Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 16)

(Contd. of page 15)

· **Sources**
www.gestis.de
www.echa.eu
logkow.cisti.nrc.ca

· *** Data compared to the previous version altered.**