




WestWood 900 Catalyst

Catalyst Powder

Also known as **ALT Catalyst Powder**

Product No. 900-000-905 - 0.5 kg box
Product No. 900-000-020 - 2.0 kg box
Product No. 900-000-512 - 5.0 kg box
Product No. 900-000-000 - 25.0 kg box



PRODUCT PACKAGING QUANTITY

0.5, 2.0, 5.0, and 25 KG boxes

PRODUCT DESCRIPTION

WestWood 900 catalyst powder is a reactive agent used to initiate and control the curing of WestWood PMMA resins. When blended with the resin, it activates the curing process and regulates the reaction speed. The amount of catalyst required varies with ambient temperature and directly affects the cure time.

ADDITIONAL INFORMATION

Refer to specific product data sheets for information regarding substrate preparation, coverage rates, working times, mixing and catalyst quantities, and application temperatures.

STORAGE

WestWood 900 catalyst powder must be stored in sealed containers in dry, cool areas away from heat, ignition sources, and direct sunlight. Storage temperatures should remain below 77°F (25°C). When kept in its original packaging under proper conditions, the product has a minimum shelf life of six months. Exposure to heat may cause clumping and reduce effectiveness. At elevated temperatures, such as those caused by direct sunlight, powder may self-ignite. Direct sun exposure should be strictly avoided on site.

DISPOSAL

All waste and packaging must be disposed of in accordance with local regulations. Do not discard in landfills or allow product to enter the sewage system. If recycling is not possible, treat waste as hazardous and arrange for proper disposal through authorized channels.

Empty containers must be free of residue before disposal. Partially filled or contaminated packaging must be handled in coordination with regional waste authorities and in full compliance with applicable regulations.