



WestWood Cleaner

Also known as **ALT Activator/Cleaner**

Product No. 3001185 - 1 gal (3.78 L) can

Product No. 3001184 - 5 gal (18.9 L) can

PRODUCT DESCRIPTION

WestWood Cleaner is a clear, aromatic blended solvent used to clean and reactivate cured membrane surfaces at tie-ins, repairs, and between staged resin coats. WestWood Cleaner also serves as a general-purpose solvent for cleaning metal and plastic surfaces before resin application, and for removing spills or cleaning tools and equipment.

APPLICATION INFORMATION

WestWood Cleaner should be wiped onto the existing membrane and allowed to evaporate for 20 minutes. The area must be over-coated within 60 minutes of application. Only treat areas that can be coated within this 60-minute window. Reapply as needed to ensure proper reactivation of all transition areas.


STORAGE

Always store in cool and dry location. Do not store in direct sunlight or in temperatures above 77°F (25°C). Flammable, keep away from heat, sparks, and open flames.

DISPOSAL

WestWood Cleaner is considered a hazardous material and must be handled as such, in accordance with local, state, and federal regulations. Refer to product safety data sheet (SDS) for additional information, and prior to handling or use.

WestWood Fleece is a non-woven, chopped strand polyester fabric used in cold fluid-applied reinforced membrane systems to enhance tear strength, puncture resistance, and crack-bridging performance while maintaining membrane uniformity.



PRODUCT PACKAGING QUANTITY

1 gal and 5 gal resealable can